



Ansutek Security Product Catalogue

Release Date 08 Sept 2010











**POS Cameras - DVR's - Long Range Outdoor Cameras
Vandal Proof Cameras - Network IP & PTZ Cameras - Analogue
PTZ Wired Dome IP Cameras - CCTV Kits/Cameras - PC Cards
and More...**

**Ph: 0800 722 648 - email: security@ansutek.co.nz
www.ansutek.co.nz**

Note: All pricing in this catalogue is subject to alteration without prior notice and excludes GST

POS Cameras - POS Cameras / DVR's

Model		Description	Price
FV-802D		1/3 Sony CCD camera, 420TVL, len: 4-9mm,black colour with adapter black colour.	\$169.87
FV-802 12pcs led		1/3 Sony CCD camera, 420TVL, len: 3.6mm,black colour 12pcs led with adapter black colour.	\$109.12
FV-705		1/3 Sony CCD camera, 420TVL, len: 3.6mm,black colour ,with bracket and adapter.	\$113.84
FV-828		1/3 Sony CCD camera, 420TVL, len: 3.6mm,black colour with adapter.	\$99.04
FV-P01		Australia style stand adapter 500MA 12V for QF-802	\$45.00
FV-P02		Australia style stand adapter 1000MA 12V for QF-802D	\$45.00
FV-9004		H.264 4CH DVR with VGA, wih internation	\$462.97
FV-9008		H.264 8CH DVR with VGA, wih internation	\$666.66
FV-9216		H.264 16CH DVR with VGA, wih internation	\$1,127.65



Long Range - Outdoor Cameras

Model		Description	Price
CW1707-SCX/P		Weatherproof Day/ Night IR Cannon Camera, 1/3" Sony HQ1 520TVL CCD, Color, 0Lux (IR On), 30 + 30 IR LEDs, 60m, 12VDC, PAL. [Note: 16mm Lens & Cable-Through Mounting Bracket Included, Size: 235mm (L) x 230mm (W) x 225mm (H)]	\$402.00
CW1905-SCX/P		Weatherproof Day & Night IR Camera, 1/3" Sony 520TVL CCD, Color, 0Lux (IR On), 24IR LEDs, 30m, 12VDC, PAL. [Note: 3.6mm Lens & Cable-Through Mounting Bracket Included, Size: 60mm (Φ) x 205mm (L)]	\$286.93
CW1058-SCX/P		Weatherproof Day & Night IR Housing Cameras With In-built Blower, 1/3" Sony HQ1 520TVL CCD, Color, 0Lux (IR On), 30IR LEDs, 40m, in-built blower, 110/220VAC, PAL. [Note: 16mm Manual Iris Lens & Mounting Bracket Included, Size: 395mm (L) x 135mm (W) x 100mm (H)]	\$346.61



Vandal Proof Cameras

Model	Description	Price
	3.5" Vandal-proof Vari-focal Dome Cameras [CV3121 series]. 4-9mm Manual Zoom Lens, IP55, 3-AXIS Internal Bracket, 12VDC, Size: 117mm (Φ) x 92mm (H), Weight: 750g.	
CV3121-SCU	1/3" Sony CCD + Sony DSP, 550TVL, 0.001Lux	\$264.77
CV3121-NCSS	1/3" Sony CCD + Nextchip DSP, 540TVL, Low Lux, 0.001Lux	\$236.18
CV3121-NCS	1/3" Sony CCD + Nextchip DSP, 540TVL, 0.1Lux	\$225.46
CV3121-SCCS	1/3" Sony CCD + Sony DSP, 420TVL, Low Lux, 0.001Lux	\$179.01
CV3121-SCC	1/3" Sony CCD + Sony DSP, 420TVL, 0.8Lux	\$171.86
CV3121-HAC	1/4" Sharp CCD + Sharp DSP, 420TVL, 0.8Lux	\$153.99
	4.5" Vandal-proof Vari-focal Dome Cameras [CV3122 series], 4-9mm Manual Zoom Lens, IP55, 3-AXIS Internal Bracket, 12VDC, Size: 142mm (Φ) x 100mm (H), Weight: 950g.	
CV3122-SCU	1/3" Sony CCD + Sony DSP, 550TVL, 0.001Lux	\$282.64
CV3122-NCSS	1/3" Sony CCD + Nextchip DSP, 540TVL, Low Lux, 0.001Lux	\$257.63
CV3122-NCS	1/3" Sony CCD + Nextchip DSP, 540TVL, 0.1Lux	\$246.90
CV3122-SCCS	1/3" Sony CCD + Sony DSP, 420TVL, Low Lux, 0.001Lux	\$200.45
CV3122-SCC	1/3" Sony CCD + Sony DSP, 420TVL, 0.8Lux	\$193.30
CV3122-HAC	1/4" Sharp CCD + Sharp DSP, 420TVL, 0.8Lux	\$171.86

Vandal Proof Cameras (cont)

Model	Description	Price
	Vandal-proof IR Dome Cameras [CV3123 series] 3.6mm Board Lens, IP55, 24pcs IR LEDs, Max. 20m, 12VDC, Size: 100mm (Φ) x 80mm (H), Weight: 800g.	
CV3123-NCSS	1/3" Sony CCD + Nextchip DSP, 540TVL, Low Lux, 0Lux (IR On)	\$218.32
CV3123-NCS	1/3" Sony CCD + Nextchip DSP, 540TVL, 0Lux (IR On)	\$204.02
CV3123-SCCS	1/3" Sony CCD + Sony DSP, 420TVL, Low Lux, 0Lux (IR On)	\$157.57
CV3123-SCC	1/3" Sony CCD + Sony DSP, 420TVL, 0Lux (IR On)	\$150.42
CV3123-HAC	1/4" Sharp CCD + Sharp DSP, 420TVL, 0Lux (IR On)	\$132.55
	Vandal-proof Vari-focal IR Dome Cameras [CV3124 series] 4-9mm Manual Zoom Lens, IP55, 21pcs IR LEDs, Max. 20m, 3-AXIS Internal Bracket, 12VDC, Size: 149mm (Φ) x 99mm (H), Weight: 1300g.	
CV3124-SCU	1/3" Sony CCD + Sony DSP, 550TVL, 0Lux (IR On)	\$282.64
CV3124-NCSS	1/3" Sony CCD + Nextchip DSP, 540TVL, Low Lux, 0Lux (IR On)	\$264.77
CV3124-NCS	1/3" Sony CCD + Nextchip DSP, 540TVL, 0Lux (IR On)	\$250.48
CV3124-SCCS	1/3" Sony CCD + Sony DSP, 420TVL, Low Lux, 0Lux (IR On)	\$204.02
CV3124-SCC	1/3" Sony CCD + Sony DSP, 420TVL, 0Lux (IR On)	\$196.88
CV3124-HAC	1/4" Sharp CCD + Sharp DSP, 420TVL, 0Lux (IR On)	\$182.58

Vandal Proof Cameras (cont)

Model	Description	Price
	Vandal-proof Vari-focal Dome Cameras [CV3125 series] 4-9mm Manual Zoom Lens, IP55, 3-AXIS Internal Bracket, 12VDC, Size: 140mm (Φ) x 94mm (H), Weight: 850g.	
CV3125-SCU	1/3" Sony CCD + Sony DSP, 550TVL, 1.0Lux	\$264.77
CV3125-NCSS	1/3" Sony CCD + Nextchip DSP, 540TVL, Low Lux, 0.001Lux	\$243.33
CV3125-NCS	1/3" Sony CCD + Nextchip DSP, 540TVL, 1.0Lux	\$229.04
CV3125-SCCS	1/3" Sony CCD + Sony DSP, 420TVL, Low Lux, 0.001Lux	\$186.15
CV3125-SCC	1/3" Sony CCD + Sony DSP, 420TVL, 0.8Lux	\$179.01
CV3125-HAC	1/4" Sharp CCD + Sharp DSP, 420TVL, 1.0Lux	\$153.99
	Vandal-proof Vari-focal IR Dome Cameras [CV3127 series] 4-9mm Manual Zoom Lens, IP55, 36pcs IR LEDs, Max. 30m, 12VDC, Size: 150mm (Φ) x 120mm (H), Weight: 1100g.	
CV3127-NCSS	1/3" Sony CCD + Nextchip DSP, 540TVL, Low Lux, 0Lux (IR On)	\$313.01
CV3127-NCS	1/3" Sony CCD + Nextchip DSP, 540TVL, 0Lux (IR On)	\$302.29
CV3127-SCCS	1/3" Sony CCD + Sony DSP, 420TVL, Low Lux, 0Lux (IR On)	\$266.56
CV3127-SCC	1/3" Sony CCD + Sony DSP, 420TVL, 0Lux (IR On)	\$259.41
CV3127-HAC	1/4" Sharp CCD + Sharp DSP, 420TVL, 0Lux (IR On)	\$245.12

Network IP & PTZ Cameras

Model	Description	Price
-------	-------------	-------

Wireless Indoor Box IP Camera with SD slot (CMOS)



Resolution: VGA 640x480;
 Video compression: standard H.264 Main profile;
 Dual-streaming:H.264 and MJPEG;
 Audio In: 1-ch linear input;
 Audio Out: 1-ch RCA interface linear output;
 Two-way voice; Built-in Mic;
 Built in WIFI (802.11B/G);
 Built in SD card slot for recording
 Sensor: 1/4" CMOS, 1.0Lux
Accessories: Power supply, Antenna, Lens not included but Optional

CN1210-WS	Sensor: 1/4" CMOS, 1.0Lux	\$283.09
-----------	---------------------------	----------

Wireless Indoor Box IP Camera with SD slot (CCD)



Resolution: Full D1, PAL:704x576 ;NTSC:704x480;
 Video Frame: 25fps(PAL) / 30fps (NTSC);
 Video compression:standard H.264 Main profile;
 Dual-streaming:H.264 and MJPEG;
 Audio In: 1-ch linear input;
 Audio Out: 1-ch RCA interface linear output;
 Two-way voice; Built-in Mic;
 Built in WIFI (802.11B/G);
 Built in SD card slot for recording
Accessories: Power supply, Antenna, Lens not included but Optional

CN1210-SCC-WS	Sensor: 420TVL, 0.5Lux, 1/3" SONY CCD	\$326.76
CN1210-SCH-WS	Sensor: 500TVL, 0.5Lux, 1/3" SONY Super HAD CCD	\$376.40
CN1210-SCX-WS	Sensor: 520TVL, 0.5Lux, 1/3" SONY Super HAD CCD	\$406.18
CN1210-SCU-WS	Sensor: 540TVL, 0.5Lux, 1/3" SONY Exview HAD CCD	\$475.66

Network IP & PTZ Cameras (cont)

Model	Description	Price
-------	-------------	-------

Wireless Indoor Dome IP Camera with Wifi, SD slot, IR LEDs



Resolution: Full D1, PAL:704x576; NTSC:704x480;
Video Frame: 25fps(PAL) / 30fps (NTSC);
Video compression: standard H.264 Main profile;
Dual-streaming: H.264 and MJPEG;
IR LEDs: 16pcs, IR distance: Max. 10m;
Audio In: 1-ch linear input;
Audio Out: 1-ch RCA interface linear output;
Two-way voice;
Built in WIFI (802.11b/g);
Built in SD card slot for recording

Accessories: Power supply, Antenna, Lens included
(6mm/8mm/12mm fixed lens optional)

CN1212-SCC-WSR	Sensor: 420TVL, 1/3" SONY CCD; Color: 0.3Lux, B&W: 0.01Lux, Infrared: 0 Lux	\$645.35
CN1212-SCH-WSR	Sensor: 500TVL, 1/3" SONY Super HAD CCD; Color: 0.3Lux, B&W: 0.01Lux, Infrared: 0 Lux	\$734.69
CN1212-SCX-WSR	Sensor: 520TVL, 1/3" SONY Super HAD CCD; Color: 0.3Lux, B&W: 0.01Lux, Infrared: 0 Lux	\$777.57
CN1212-SCU-WSR	Sensor: 540TVL, 1/3" SONY Exview HAD CCD; Color: 0.3Lux, B&W: 0.01Lux, Infrared: 0 Lux	\$884.78

Wireless Pan Tilt IP Camera with WiFi, SD slot



Sensor: 1/4" CMOS Sensor, 1.0Lux; Resolution: VGA;
Video Frame: 25fps(PAL) / 30fps (NTSC);
Video compression: standard H.264 Main profile;
IR lights: 10pcs, IR distance 3-5 meters;
Dual-streaming: H.264 and MJPEG;
Audio In: 1-ch linear input;
Audio Out: 1-ch RCA interface linear output;
Two-way voice; Built-in P/T, level 320°; vertical :110°;
Built in WIFI (802.11B/G) and SD card slot for recording.

Accessories: Power supply, Lens included

CN1206-WSR		\$598.90
------------	--	----------

Analogue Mini PTZ Cameras

Model	Description	Price
-------	-------------	-------

Mini 4" PTZ 100X Zoom High Speed Dome Camera (Samsung 10X D/N)

- Incorporates features from full size PTZ speed dome
- Using Samsung SDM-100P D/N Camera
- 100X Zoom (10X Optical, 10X Digital)
- Auto / Manual / Semi-auto focus
- 0.7 Lux (Color)/ 0.02 Lux (B/W)
- Angle of Movement - Pan: 360° (Endless), Tilt:180° (Auto-Flip), 95° (Normal)
- Speed of Movement: 360°/sec Max.
- 0.05°/ sec Pan/ Tilt Speed available
- 4 Pattern, 8 Group, 8 Swing Cruise Trajectory Line
- 127 Presets, RS485, Support Pelco-D, Pelco-P
- Day / Night Function
- On-Screen Display Menu
- 12VDC / 24VAC Dual Voltage
- 141mm (φ) x 120mm (H)
- Optional Mounts: Surface mount, Indoor & Outdoor Wall mount

CS84A-10N-S
(Surface Mount)



\$891.79

CS84A-10N-V
(Indoor Wall Mount)



\$963.26

CS84A-10N-W
(Outdoor Wall Mount)

\$991.85

Analogue Mini PTZ Cameras (cont)

Model	Description	Price
-------	-------------	-------

CS84C Series - Mini 4" High Speed Dome Camera - Indoor Surface Mount

- Indoor surface mount installation
- Al-alloy, 4 inch transparent dome cover
- Manual control speed: 0.1° - 150°/sec for pan, 0.1° - 80°/sec for tilt
- Preset target speed: 250°/sec for pan, 100°/sec for tilt
- 128 preset positions
- Accurate motor driving, stable operation, accurate orientation
- Built-in menu, by which can set the camera, pan & tilt parameter
- Track memory function
- 8 preset tour routes
- Embed in surge and lightning protector
- Compatible PELCO "P", "D" protocol
- Meeting IP40, CE, ROHS, FCC standards

CS84C-10N-S
(Samsung 10X D/N
module)



\$1,077.62

CS84C-10NL-S
(Sony 10X D/N module)

\$1,342.06

Analogue Mini PTZ Cameras (cont)

Model	Description	Price
-------	-------------	-------

CS84C Series - Mini 4" High Speed Dome Camera - Indoor Pendant

- Indoor pendant installation
- Al-alloy, 4 inch transparent dome cover
- Manual control speed: 0.1° - 150°/sec for pan, 0.1° - 80°/sec for tilt
- Preset target speed: 250°/sec for pan, 100°/sec for tilt
- 128 preset positions
- Accurate motor driving, stable operation, accurate orientation
- Built-in menu, by which can set the camera, pan & tilt parameter
- Track memory function
- 8 preset tour routes
- Embed in surge and lightning protector
- Compatible PELCO "P", "D" protocol
- Meeting IP40, CE, ROHS, FCC standards

* Default pendant mount bracket model no.: AS-110

CS84C-10N-P
(Samsung 10X D/N
module)



\$1,120.50

CS84C-10NL-P
(Sony 10X D/N module)



\$1,384.94

Analogue Mini PTZ Cameras (cont)

Model	Description	Price
-------	-------------	-------

CS84C Series - Mini 4" High Speed Dome Camera - Indoor Wall Mount

- Indoor wall mount installation
- Al-alloy, 4 inch transparent dome cover
- Manual control speed: 0.1°- 150°/sec for pan, 0.1°- 80°/sec for tilt
- Preset target speed: 250°/sec for pan, 100°/sec for tilt
- 128 preset positions
- Accurate motor driving, stable operation, accurate orientation
- Built-in menu, by which can set the camera, pan & tilt parameter
- Track memory function
- 8 preset tour routes
- Embed in surge and lightning protector
- Compatible PELCO "P", "D" protocol
- Meeting IP40, CE, ROHS, FCC standards

* Default wall mount bracket model no.: AS-102

CS84C-10N-V
(Samsung 10X D/N
module)



\$1,109.78

CS84C-10NL-V
(Sony 10X D/N module)



\$1,374.22

Analogue Mini PTZ Cameras (cont)

Model	Description	Price
-------	-------------	-------

CS84C Series - Mini 4" High Speed Dome Camera - Outdoor Wall Mount

- Outdoor wall mount installation
- Al-alloy, 4 inch transparent dome cover
- Manual control speed: 0.1° - 150°/sec for pan, 0.1° - 80°/sec for tilt
- Preset target speed: 250°/sec for pan, 100°/sec for tilt
- 128 preset positions
- Accurate motor driving, stable operation, accurate orientation
- Built-in menu, by which can set the camera, pan & tilt parameter
- Track memory function
- 8 preset tour routes
- Embed in surge and lightning protector
- Compatible PELCO "P", "D" protocol
- Meeting IP66, CE, ROHS, FCC standards

* Default wall mount bracket model no.: AS-102

CS84C-10N-W
(Samsung 10X D/N
module)



\$1,131.22

CS84C-10NL-W
(Sony 10X D/N module)



\$1,392.09

Analogue Mini PTZ Cameras (cont)

Model	Description	Price
-------	-------------	-------

CS86C Series - 6" integrated High Speed Dome Camera - Outdoor Wall Mount

- Outdoor wall mount installation
- Completely 6" metal material structure, strong and durable
- RS485 feedback the pan/ tilt orientation
- Change speed proportionally on Pan/ tilt speed and zoom ratio of the zoom lens
- Manual control speed: 0.1°- 150°/sec for pan, 0.1°- 80°/sec for tilt
- Preset target speed: 300°/sec for pan, 100°/sec for tilt
- 128 preset positions
- Accurate motor driving, stable operation, accurate orientation
- Built-in menu, by which can set the camera, pan & tilt parameter
- 7 alarm inputs, 2 Aux outputs
- Embed in surge and lightning protector, built-in fans and heater
- Compatible PELCO "P", "D" protocol
- Meeting IP66, CE, ROHS, FCC standards

* Default wall mount bracket model no.: AS-102



CS86C-18C-W (Sony 18x Color)	\$1,599.35
CS86C-18N-W (Sony 18x D/N)	\$1,881.66
CS86C-26N-W (Sony 26x D/N)	\$2,010.31
CS86C-36N-W (Sony 36x D/N)	\$2,260.46
CS86C-22C-W (Hitachi 22x Color)	\$1,652.96
CS86C-23N-W (Hitachi 23x D/N)	\$1,878.09
CS86C-30N-W (Hitachi 30x D/N)	\$2,153.25
CS86C-22N-W (CNB 22x D/N)	\$1,470.71
CS86C-27N-W (LG 27x D/N)	\$1,706.56

Analogue Mini PTZ Cameras (cont)

Model	Description	Price
-------	-------------	-------

CS86C1 Series Integrated High Speed Dome Camera - Indoor In-Ceiling

- Indoor in-ceiling installation
- Al-alloy 6" transparent dome cover
- Manual control speed: 0.1°- 150°/sec for pan, 0.1°- 80°/sec for tilt
- Preset target speed: 250°/sec for pan, 100°/sec for tilt
- 128 preset positions
- Accurate motor driving, stable operation, accurate orientation
- Built-in menu, by which can set the camera, pan & tilt parameter
- Track memory function
- 8 preset tour routes
- 7 alarm inputs, 2 Aux outputs
- Embed in surge and lightning protector
- Compatible PELCO "P", "D" protocol
- Meeting IP40, CE, ROHS, FCC standards



CS86C1-22C-H (Hitachi 22x Color)	\$1,545.75
CS86C1-22CL-H (Hitachi 22x Low Lux)	\$1,785.18
CS86C1-23N-H (Hitachi 23x D/N)	\$1,903.10
CS86C1-30N-H (Hitachi 30x D/N)	\$2,063.91
CS86C1-18C-H (Sony 18x color)	\$1,527.88
CS86C1-18N-H (Sony 18X D/N)	\$1,785.18
CS86C1-26N-H (Sony 26X D/N)	\$1,920.97
CS86C1-36N-H (Sony 36X D/N)	\$2,171.12
CS86C1-27N-H (LG 27X D/N)	\$1,635.09

Analogue Mini PTZ Cameras (cont)

Model	Description	Price
-------	-------------	-------

CS86C1 Series Integrated High Speed Dome Camera - Indoor Pendant

- Indoor pendant installation
- Al-alloy 6" transparent dome cover
- Manual control speed: 0.1° - 150°/sec for pan, 0.1° - 80°/sec for tilt
- Preset target speed: 250°/sec for pan, 100°/sec for tilt
- 128 preset positions
- Accurate motor driving, stable operation, accurate orientation
- Built-in menu, by which can set the camera, pan & tilt parameter
- Track memory function
- 8 preset tour routes
- 7 alarm inputs, 2 AUX outputs
- Embed in surge and lightning protector
- Compatible PELCO "P", "D" protocol
- Meeting IP40, CE, ROHS, FCC standards

* Default pendant mount bracket model no.: AS-110



CS86C1-22C-P (Hitachi 22x Color)	\$1,592.21
CS86C1-22CL-P (Hitachi 22x Low Lux)	\$1,831.63
CS86C1-23N-P (Hitachi 23x D/N)	\$1,938.84
CS86C1-30N-P (Hitachi 30x D/N)	\$2,099.65
CS86C1-18C-P (Sony 18x color)	\$1,570.76
CS86C1-18N-P (Sony 18X D/N)	\$1,813.76
CS86C1-26N-P (Sony 26X D/N)	\$1,956.71
CS86C1-36N-P (Sony 36X D/N)	\$2,206.85
CS86C1-27N-P (LG 27X D/N)	\$1,677.97

Analogue Mini PTZ Cameras (cont)

Model	Description	Price
-------	-------------	-------

CS86C1 Series Integrated High Speed Dome Camera - Indoor Wall Mount

- Indoor wall mount installation
- Al-alloy 6" transparent dome cover
- Manual control speed: 0.1°- 150°/sec for pan, 0.1°- 80°/sec for tilt
- Preset target speed: 250°/sec for pan, 100°/sec for tilt
- 128 preset positions
- Accurate motor driving, stable operation, accurate orientation
- Built-in menu, by which can set the camera, pan & tilt parameter
- Track memory function
- 8 preset tour routes
- 7 alarm inputs, 2 AUX outputs
- Embed in surge and lightning protector
- Compatible PELCO "P", "D" protocol
- Meeting IP40, CE, ROHS, FCC standards

* Default wall mount bracket model no.: AS-102



CS86C1-22C-V (Hitachi 22x Color)	\$1,581.49
CS86C1-22CL-V (Hitachi 22x Low Lux)	\$1,820.91
CS86C1-23N-V (Hitachi 23x D/N)	\$1,928.12
CS86C1-30N-V (Hitachi 30x D/N)	\$2,088.93
CS86C1-18C-V (Sony 18x color)	\$1,560.04
CS86C1-18N-V (Sony 18X D/N)	\$1,803.04
CS86C1-26N-V (Sony 26X D/N)	\$1,942.41
CS86C1-36N-V (Sony 36X D/N)	\$2,188.99
CS86C1-27N-V (LG 27X D/N)	\$1,667.25

Analogue Mini PTZ Cameras (cont)

Model	Description	Price
-------	-------------	-------

CS86C1 Series Integrated High Speed Dome Camera - Outdoor Wall Mount

- Outdoor wall mount installation
- Al-alloy 6" transparent dome cover
- Manual control speed: 0.1°- 150°/sec for pan, 0.1°- 80°/sec for tilt
- Preset target speed: 250°/sec for pan, 100°/sec for tilt
- 128 preset positions
- Accurate motor driving, stable operation, accurate orientation
- Built-in menu, by which can set the camera, pan & tilt parameter
- Track memory function
- 8 preset tour routes
- 7 alarm inputs, 2 AUX outputs
- Embed in surge and lightning protector
- Compatible PELCO "P", "D" protocol
- Meeting IP66, CE, ROHS, FCC standards

* Default wall mount bracket model no.: AS-102



CS86C1-22C-W (Hitachi 22x Color)	\$1,592.21
CS86C1-22CL-W (Hitachi 22x Low Lux)	\$1,831.63
CS86C1-23N-W (Hitachi 23x D/N)	\$1,938.84
CS86C1-30N-W (Hitachi 30x D/N)	\$2,099.65
CS86C1-18C-W (Sony 18x color)	\$1,570.76
CS86C1-18N-W (Sony 18X D/N)	\$1,813.76
CS86C1-26N-W (Sony 26X D/N)	\$1,956.71
CS86C1-36N-W (Sony 36X D/N)	\$2,206.85
CS86C1-27N-W (LG 27X D/N)	\$1,677.97

Analogue Mini PTZ Cameras (cont)

Model	Description	Price
-------	-------------	-------

CS86C2 Series - 6" integrated High Speed Dome Camera - Indoor In-Ceiling Mount

- Indoor in-ceiling installation
- Al-alloy 6" transparent dome cover
- Manual control speed: 0.1° - 150°/sec for pan, 0.1° - 80°/sec for tilt
- Preset target speed: 200°/sec for pan, 100°/sec for tilt
- 128 preset positions
- Accurate motor driving, stable operation, accurate orientation
- Embed in surge and lightning protector
- Compatible PELCO "P", "D" protocol
- Meeting IP40, CE, ROHS, FCC standards



CS86C2-22C-H (Hitachi 22X Color)	\$1,438.54
CS86C2-22CL-H (Hitachi 22X Color Low Lux)	\$1,677.97
CS86C2-23N-H (Hitachi 23X D/N)	\$1,785.18
CS86C2-18C-H (Sony 18X Color)	\$1,420.68
CS86C2-18N-H (Sony 18X D/N)	\$1,677.97
CS86C2-27N-H (LG 27X D/N)	\$1,527.88

Analogue Mini PTZ Cameras (cont)

Model	Description	Price
-------	-------------	-------

CS86C2 Series - 6" integrated High Speed Dome Camera - Indoor Surface Mount

- Indoor surface mount installation
- Al-alloy 6" transparent dome cover
- Manual control speed: 0.1° - 150°/sec for pan, 0.1° - 80°/sec for tilt
- Preset target speed: 200°/sec for pan, 100°/sec for tilt
- 128 preset positions
- Accurate motor driving, stable operation, accurate orientation
- Embed in surge and lightning protector
- Compatible PELCO "P", "D" protocol
- Meeting IP40, CE, ROHS, FCC standards



CS86C2-22C-S (Hitachi 22X Color)	\$1,438.54
CS86C2-22CL-S (Hitachi 22X Color Low Lux)	\$1,677.97
CS86C2-23N-S (Hitachi 23X D/N)	\$1,785.18
CS86C2-18C-S (Sony 18X Color)	\$1,420.68
CS86C2-18N-S (Sony 18X D/N)	\$1,677.97
CS86C2-27N-S (LG 27X D/N)	\$1,527.88

Analogue Mini PTZ Cameras (cont)

Model	Description	Price
-------	-------------	-------

CS86C2 Series - 6" integrated High Speed Dome Camera - Indoor Pendant

- Indoor pendant installation
- Al-alloy 6" transparent dome cover
- Manual control speed: 0.1° - 150°/sec for pan, 0.1° - 80°/sec for tilt
- Preset target speed: 200°/sec for pan, 100°/sec for tilt
- 128 preset positions
- Accurate motor driving, stable operation, accurate orientation
- Embed in surge and lightning protector
- Compatible PELCO "P", "D" protocol
- Meeting IP40, CE, ROHS, FCC standards

* Default pendant mount bracket model no.: AS-110



CS86C2-22C-P (Hitachi 22X Color)	\$1,503.00
CS86C2-22CL-P (Hitachi 22X Color Low Lux)	\$1,742.43
CS86C2-23N-P (Hitachi 23X D/N)	\$1,849.63
CS86C2-18C-P (Sony 18X Color)	\$1,481.56
CS86C2-18N-P (Sony 18X D/N)	\$1,742.43
CS86C2-27N-P (LG 27X D/N)	\$1,588.76

Analogue Mini PTZ Cameras (cont)

Model	Description	Price
-------	-------------	-------

CS86C2 Series - 6" integrated High Speed Dome Camera - Indoor Wall Mount

- Indoor wall mount installation
- Al-alloy 6" transparent dome cover
- Manual control speed: 0.1° - 150°/sec for pan, 0.1° - 80°/sec for tilt
- Preset target speed: 200°/sec for pan, 100°/sec for tilt
- 128 preset positions
- Accurate motor driving, stable operation, accurate orientation
- Embed in surge and lightning protector
- Compatible PELCO "P", "D" protocol
- Meeting IP40, CE, ROHS, FCC standards

* Default wall mount bracket model no.: AS-102



CS86C2-22C-V (Hitachi 22X Color)	\$1,492.28
CS86C2-22CL-V (Hitachi 22X Color Low Lux)	\$1,731.71
CS86C2-23N-V (Hitachi 23X D/N)	\$1,838.91
CS86C2-18C-V (Sony 18X Color)	\$1,470.84
CS86C2-18N-V (Sony 18X D/N)	\$1,731.71
CS86C2-27N-V (LG 27X D/N)	\$1,578.04

Analogue Mini PTZ Cameras (cont)

Model	Description	Price
-------	-------------	-------

CS86C2 Series - 6" integrated High Speed Dome Camera - Outdoor Wall Mount

- Outdoor wall mount installation
- Al-alloy 6" transparent dome cover
- Manual control speed: 0.1° - 150°/sec for pan, 0.1° - 80°/sec for tilt
- Preset target speed: 200°/sec for pan, 100°/sec for tilt
- 128 preset positions
- Accurate motor driving, stable operation, accurate orientation
- Embed in surge and lightning protector
- Compatible PELCO "P", "D" protocol
- Meeting IP40, CE, ROHS, FCC standards

* Default wall mount bracket model no.: AS-102



CS86C2-22C-W (Hitachi 22X Color)	\$1,528.01
CS86C2-22CL-W (Hitachi 22X Color Low Lux)	\$1,767.44
CS86C2-23N-W (Hitachi 23X D/N)	\$1,874.65
CS86C2-18C-W (Sony 18X Color)	\$1,506.57
CS86C2-18N-W (Sony 18X D/N)	\$1,767.44
CS86C2-27N-W (LG 27X D/N)	\$1,613.78

Analogue Mini PTZ Cameras (cont)

Model	Description	Price
-------	-------------	-------

2-Dimensional & 3-Dimensional Control Keyboards

2-D Control Keyboard

- Pelco "P" protocol, baud rate: 4800, RJ-45 interface
- The key stroke on the keyboard can control the camera's address switch
- Can transfer the dome function menu
- Can dispose presets position
- Open & close iris, Lens zooming and focusing, start & stop the auto/ random scan function



AK-200

\$415.32

3-D Control Keyboard






- Can control the camera or pan& tilt rotation, zoom, iris, focus and parameter setting
- RS485 control signal can connect to max. 255 pcs integrated dome camera
- Support to PELCO-D, PELCO-P protocol
- LCD display menu, three-axis joystick, DVR and alarm control
- Baud rate: 2400/ 4800/ 9600/ 19200
- Communication distance: 1200m (0.5mm twisted pairs)
- Power supply: 9~12VDC, 5W
- Environment temperature: 00 C -+400 C
- Humidity: less than 90%



AK-300

\$679.76

Analogue Mini PTZ Cameras (cont)

Model	Description	Price
Accessories for Speed Dome Camera		
AS-101	 <p>Outdoor wall mount long bracket Material: Aluminum-alloy Installation: Wall mount Maximum Loading weight: 50kg Environment: Outdoor, Indoor Application: Indoor/ outdoor pendant, wall mount speed dome camera</p>	\$130.76
AS-102	 <p>Outdoor wall mount bracket Material: Aluminum-alloy Installation: Wall suspended Maximum Loading Weight: 40kg Environment: Outdoor, Indoor Application: Indoor/ outdoor pendant, wall mount speed dome camera</p>	\$80.74
AS-103	 <p>Outdoor wall mount bracket Material: Aluminum-alloy Installation: Wall suspended Maximum Loading Weight: 40kg Environment: Outdoor, Indoor Application: Indoor/ outdoor pendant, wall mount speed dome camera</p>	\$111.11
AS-104	 <p>Surface mount adapter Material: Zinc board Installation: Wall mount suspended Environment: Outdoor, Indoor Application: Match with brackets AS-102 or AS-112</p>	\$85.96
AS-105	 <p>Pole mount adapter Material: Zinc board Installation: Wall mount suspended Environment: Outdoor, Indoor Application: Match with brackets AS-102 or AS-112</p>	\$94.90

Analogue Mini PTZ Cameras (cont)

Model	Description	Price
-------	-------------	-------

Accessories for Speed Dome Camera (cont)

AS-106



24VAC Power supply box for high speed dome camera

Material: Aluminum-alloy
Input Voltage: 110 VAC or 220 VAC
Output Voltage: 24 VAC, 2.5A

\$112.76

AS-108



Outdoor bracket with 24VAC Power supply box

Material: Aluminum-alloy
Installation: Wall mount bracket, with power supply box
Maximum Loading Weight: 40kg
Environment: Outdoor, Indoor
Application: Indoor/ outdoor pendant, wall mount speed dome camera

\$169.94

AS-109



Indoor suspended pendant bracket (40cm)

Material: Aluminum-alloy
Installation: Suspended mount (40cm)
Maximum Loading weight: 10kg
Environment: Indoor
Application: Indoor pendant mount speed dome camera

\$87.75

AS-110



Indoor suspended pendant bracket (20cm)

Material: Aluminum-alloy
Installation: Suspended mount (20cm)
Maximum Loading weight: 10kg
Environment: Indoor
Application: Indoor pendant mount speed dome camera

\$73.46

Wired Dome IP Cameras

Model	Description	Price
-------	-------------	-------

Wired Indoor/ Outdoor High Speed Dome IP Camera



Resolution: Full D1, PAL:704x576 ;NTSC:704x480;
Video Frame: 25fps(PAL) / 30fps (NTSC);
Video compression: standard H.264 Main profile;
Dual-streaming: H.264 and MJPEG;
Angle: level 360° ,vertical 180 ° ;
Speed: level 0.1°-150°/S, vertical 0.1°-100°/S;
Preset Position: 128;
Audio In: 1-ch linear input;
Audio Out: 1-ch RCA interface linear output;
Two-way voice; IP66 Standard for outdoor using;

Accessories: Power supply, Lens, PTZ, Bracket included

CN1203A-L16	Sensor: 1/4" SONY Super HAD CCD, up to 480TVL, Color: 1.0Lux, B&W: 0.01Lux Zoom: LG 16X optical; 8X digital	\$1,989.00
CN1203A-L27	Sensor: 1/4" SONY Super HAD CCD, up to 480TVL, Color: 1.0Lux, B&W: 0.01Lux Zoom: LG 27X optical; 10X digital	\$2,314.19
CN1203A-S18	Sensor: 1/4" SONY Super HAD CCD, up to 480TVL, Color: 0.5Lux, B&W: 0.001Lux Zoom: SONY 18X optical; 10X digital	\$2,357.07
CN1203A-S26	Sensor: 1/4" SONY Super HAD CCD, up to 480TVL, Color: 0.5Lux, B&W: 0.001Lux Zoom: SONY 26X optical; 12X digital	\$2,567.91
CN1203A-S26	Sensor: 1/4" SONY Super HAD CCD, up to 480TVL, Color: 0.5Lux, B&W: 0.001Lux Zoom: SONY 36X optical; 12X digital	\$2,939.56

Wired Dome IP Cameras (cont)

Model	Description	Price
-------	-------------	-------

Wired Indoor/ Outdoor High Speed Dome IP Camera




Resolution: Full D1, PAL:704x576 ;NTSC:704x480;
Video Frame: 25fps(PAL) / 30fps (NTSC);
Video compression: standard H.264 Main profile;
Dual-streaming: H.264 and MJPEG;
Angle: level 360° ,vertical 180 ° ;
Speed: level 0.1°-150°/S, vertical 0.1°-100°/S;
Preset Position: 128;
Audio In: 1-ch linear input;
Audio Out: 1-ch RCA interface linear output;
Two-way voice; IP66 Standard for outdoor using;

Accessories: Power supply, Lens, PTZ, Bracket included

CN1203B-L16	Sensor: 1/4" SONY Super HAD CCD, up to 480TVL, Color: 1.0Lux, B&W: 0.01Lux Zoom: LG 16X optical;8X digital	\$1,674.53
CN1203B-L27	Sensor: 1/4" SONY Super HAD CCD, up to 480TVL, Color: 1.0Lux, B&W: 0.01Lux Zoom: LG 27X optical;10X digital	\$1,992.57
CN1203B-S18	Sensor: 1/4" SONY Super HAD CCD, up to 480TVL, Color: 0.5Lux, B&W: 0.001Lux Zoom: SONY 18X optical;10X digital	\$2,046.18
CN1203B-S26	Sensor: 1/4" SONY Super HAD CCD, up to 480TVL, Color: 0.5Lux, B&W: 0.001Lux Zoom: SONY 18X optical;10X digital	\$2,253.44
CN1203B-S36	Sensor: 1/4" SONY Super HAD CCD, up to 480TVL, Color: 0.5Lux, B&W: 0.001Lux Zoom: SONY 36X optical;12X digital	\$2,617.94

Wired Dome IP Cameras (cont)

Model	Description	Price
Wired Indoor/ Outdoor Low Speed Dome IP Camera		
	 <p> Resolution: Full D1, PAL:704x576 ;NTSC:704x480; Video Frame: 25fps(PAL) / 30fps (NTSC); Video compression: standard H.264 Main profile; Dual-streaming: H.264 and MJPEG; Angle: level 360° ,vertical 180 ° ; Speed: level 6°-15°/S, vertical 6°-15°/S; Preset Position: 64; Audio In: 1-ch linear input; Audio Out: 1-ch RCA interface linear output; Two-way voice; IP66 Standard for outdoor using; </p> <p>Accessories: Power supply, Lens, PTZ, Bracket included</p>	
CN1223A-L16	Sensor: 1/4" SONY Super HAD CCD, up to 480TVL, Color: 1.0Lux, B&W: 0.2Lux Zoom: LG 16X optical;8X digital	\$1,517.29
CN1223A-L27	Sensor: 1/4" SONY Super HAD CCD, up to 480TVL, Color: 1.0Lux, B&W: 0.2Lux Zoom: LG 27X optical;10X digital	\$1,778.16

Wired Dome IP Cameras (cont)

Model	Description	Price
-------	-------------	-------

Wired Indoor/ Outdoor Low Speed Dome IP Camera with IR LEDs



Resolution: Full D1, PAL:704x576 ;NTSC:704x480;

Video Frame: 25fps(PAL) / 30fps (NTSC);

Video compression: standard H.264 Main profile;

Dual-streaming: H.264 and MJPEG;

IR lights: 36pcs,IR distance 50-100 meters;

Angle: level 360° ,vertical 180 ° ;

Speed: level 6°-14°/S, vertical 6°-14°/S;

Preset Position: 64;

Audio In: 1-ch linear input;

Audio Out: 1-ch RCA interface linear output;

Two-way voice; IP66 Standard for outdoor using;

Accessories: Power supply, Lens, PTZ, Bracket included

CN1223B-S18-R	Sensor: 1/4" Color CCD, up to 480 TVL, Color: 0.7Lux, B&W: 0.001Lux. Zoom: SONY 18X optical,10X digital;	\$2,882.38
CN1223B-L23-R	Sensor: 1/4" Color CCD, up to 480 TVL, Color: 0.7Lux, B&W: 0.001Lux. Zoom: LG 23X optical,10X digital;	\$2,517.88

Wired Dome IP Cameras (cont)

Model	Description	Price
-------	-------------	-------

Wired Mini High Speed Dome IP Camera



Resolution: Full D1, PAL:704x576 ;NTSC:704x480;

Video Frame: 25fps(PAL) / 30fps (NTSC);

Video compression: standard H.264 Main profile;

Dual-streaming: H.264 and MJPEG;

Angle: level 360° ,vertical 180 ° ;

Speed: level 0.1°-150°/S, vertical 0.1°-100°/S;

Preset Position: 128;

Audio In: 1-ch linear input;

Audio Out: 1-ch RCA interface linear output;

Two-way voice; IP66 Standard for outdoor using;

Accessories: Power supply, Lens, PTZ, Bracket included

CN1213-A10	Sensor: 1/4" SONY Super HAD CCD, up to 480TVL, Color: 0.5Lux, B&W: 0.01Lux Zoom: Samsung 10X optical	\$1,813.76
CN1213-S10	Sensor: 1/4" SONY Super HAD CCD, up to 480TVL, Color: 0.5Lux, B&W: 0.01Lux Zoom: SONY 10X optical;10X digital zoom	\$2,078.21

Wired Dome IP Cameras (cont)

Model	Description	Price
-------	-------------	-------

Wireless High Speed Dome IP Camera



Resolution: Full D1, PAL:704x576 ;NTSC:704x480;

Video Frame: 25fps(PAL) / 30fps (NTSC);

Video compression: standard H.264 Main profile;

Dual-streaming: H.264 and MJPEG;

Angle: level 360° ,vertical 180 ° ;

Speed: level 0.08° - 240°/S,vertical 0.08° - 100°/S

Preset Position: 128;

Audio In: 1-ch linear input;

Audio Out: 1-ch RCA interface linear output;

Two-way voice; IP66 Standard for outdoor using;

Built in WIFI (802.11B/G)

Accessories: Power supply, Lens, PTZ, Bracket included

CN1203-L16-WS	Sensor: 1/4" SONY Super HAD CCD, up to 480TVL, Color: 1.0Lux, Zoom: LG 16X optical, 8X digital	\$2,367.79
CN1203-S18-WS	Sensor: 1/4" SONY Super HAD CCD, up to 480TVL, Color: 1.0Lux, B/W:0.01Lux Zoom: SONY 18X optical, 10X digital	\$2,725.15

CCTV Kits

Model	Description	Price
-------	-------------	-------

AP-KIT402 - 4ch, 500GB HDD



2pcs indoor cameras

Indoor IR Plastic dome 1/4"SONY COLOR CCD, 420TVL, 0LUX, 24LED, 15-30M, Lens:3.6mm



2pcs outdoor cameras

1/4"SONY 420tvl,0lux, 36 IR leds 30 meter, waterproof IP66 w/3.6mm lens, Casing could be balck or silver



1pc DVR



4channel Video Compression H.264
Real time display and record:100FPS(120FPS)
Display resolution: D1; Record resolution: CIF
HDD Interface Support 1pc x 1T SATA HDD & USB disk
Network Protocol Support TCP/IP, UDP, DHCP, DNS, PPPoE
Network Function Support to live view with IE & with Mobile phone
With VGA output

Accessories:

1pc 30meter video+power Cable
2pcs 20meter video+power Cable
1pc 10meter video+power Cable
1pc Power supply for 4 camera 12V DC 2A
1pc DVR (BNC) to SCART cable for TV connection
1pc 1 metre crossed network patch lead
2pcs A4 size CCTV notification signs

\$1,187.74

CCTV Kits (cont)

Model	Description	Price
AP-KIT405 - 4ch, 500GB HDD	 <p>4pcs indoor cameras Color 1/4"SONY, 420TVL,0LUX, 6mm Lens ,24LED≤15m, vandal proof and weather proof casing, IP66</p>  <p>1pc DVR 4channel Video Compression H.264 Real time display and record:100FPS(120FPS) Display resolution: D1; Record resolution: CIF HDD Interface Support 1pc x 1T SATA HDD & USB disk Network Protocol Support TCP/IP, UDP, DHCP, DNNS, PPPoE Network Function Support to live view with IE & with Mobile phone With VGA output</p> <p>Accessories: 1pc 30meter video+power Cable 2pcs 20meter video+power Cable 1pc 10meter video+power Cable 1pc Power supply for 4 camera 12V DC 2A 1pc DVR (BNC) to SCART cable for TV connection 1pc 1 metre crossed network patch lead 2pcs A4 size CCTV notification signs</p>	\$1,216.32

CCTV Kits (cont)

Model	Description	Price
-------	-------------	-------

AP-KIT801 - 8ch, 750GB HDD



4pcs indoor cameras

Indoor IR Plastic dome 1/4"SONY COLOR CCD, 420TVL, 0LUX, 24LED, 15-30M, Lens:3.6mm



4pcs outdoor cameras

1/4"SONY 420tvl,0lux, 36 IR leds 30 meter, waterproof IP66 w/3.6mm lens, Casing could be balck or silver



1pc DVR

8channel H264 Compressed DVR
Real time Display and Record
With Internet Function
Support one piece 1000G HDD(SATA)
Support USB stick memory backup
Support PAD, WINCE AND SYMBIAN SYSTEM Mobile phone view and control.
Support Email alarm function

Accessories:

30meter video+power Cable
2pcs 20meter video+power Cable
2pcs 10meter video+power Cable
2pc Power supply for 4 camera 12V DC 2A
1pc DVR (BNC) to SCART cable for TV connection
1pc 1 metre crossed network patch lead
4pcs A4 size CCTV notification signs

4pcs

\$1,777.37

CCTV Kits (cont)

Model	Description	Price
-------	-------------	-------

AP-KIT801 - 8ch, 750GB HDD



4pcs indoor cameras

Color 1/4"SONY, 420TVL,0LUX, 3.6mm Lens ,24LED≤15m, vandal proof and weather proof casing, IP66



4pcs outdoor cameras

1/4" SONY COLOR CCD 420tvl,0lux, 24 IR leds 30meter(100Feet), waterproof IP66 w/3.6mm lens, Cable inside bracket

1pc DVR

8channel H264 Compressed DVR

Real time Display and Record

With Internet Function

Support one piece 1000G HDD(SATA)

Support USB stick memory backup

Support PAD, WINCE AND SYMBIAN SYSTEM Mobile phone view and control.

Support Email alarm function



Accessories:

30meter video+power Cable

2pcs 20meter video+power Cable

2pcs 10meter video+power Cable

2pc Power supply for 4 camera 12V DC 2A

1pc DVR (BNC) to SCART cable for TV connection

1pc 1 metre crossed network patch lead

4pcs A4 size CCTV notification signs

4pcs

\$1,877.43

CCTV Kits (cont)

Model	Description	Price
-------	-------------	-------

AP-KIT1202 - 12ch, 1000GB HDD



6pcs indoor cameras

Color 1/4"SONY, 420TVL,0LUX, 3.6mm Lens ,24LED≤15m,
vandal proof and weather proof casing, IP66



6pcs outdoor cameras

1/4" SONY COLOR CCD 420tvl,0lux, 24 IR leds 30meter(100Feet),
waterproof IP66 w/3.6mm lens, Cable inside bracket



1pc 16ch DVR

Video Compression H.264
BNC 16ch input/2ch output, 1ch SPOT OUTPUT, 1ch VGA output
Audio Input/Output RCA 4ch input/2ch output
Real time display and record:480FPS(400FPS)
Recording Pack Time 15/30/45/60mins selectable
HDD Interface Support 2pcs x 1T SATA HDD & USB disk
Network Function Support to live view with IE & with Mobile phone
USB2.0 USB mouse, USB disk (backup, upgrade)
Sensor & Alarm I/O 16 sensor inputs / 1 alarm output

Accessories:

6pcs 30meter video+power Cable
4pcs 20meter video+power Cable
2pcs 10meter video+power Cable
1pc 12V 10A 18channel power supply box
1pc DVR (BNC) to SCART cable for TV connection
1pc 1 metre crossed network patch lead
6pcs A4 size CCTV notification signs

\$2,960.21

CCTV Kits (cont)

Model	Description	Price
-------	-------------	-------

AP-KIT1203 - 12ch, 1000GB HDD



12pcs outdoor cameras

1/4" SONY COLOR CCD 420tvl, 0lux, 24 IR leds 30meter(100Feet),
waterproof IP66 w/3.6mm lens, Cable inside bracket



1pc 16ch DVR

Video Compression H.264
BNC 16ch input/2ch output, 1ch SPOT OUTPUT, 1ch VGA output
Audio Input/Output RCA 4ch input/2ch output
Real time display and record: 480FPS(400FPS)
Recording Pack Time 15/30/45/60mins selectable
HDD Interface Support 2pcs x 1T SATA HDD & USB disk
Network Function Support to live view with IE & with Mobile phone
USB2.0 USB mouse, USB disk (backup, upgrade)
Sensor & Alarm I/O 16 sensor inputs / 1 alarm output

Accessories:

6pcs 30meter video+power Cable
4pcs 20meter video+power Cable
2pcs 10meter video+power Cable
1pc 12V 10A 18channel power supply box
1pc DVR (BNC) to SCART cable for TV connection
1pc 1 metre crossed network patch lead
6pcs A4 size CCTV notification signs

\$3,024.53

CCTV Kits (cont)

Model	Description	Price
-------	-------------	-------

AP-KIT1601 - 16ch, 1000GB HDD



4pcs indoor cameras

Indoor IR Plastic dome 1/4"SONY COLOR CCD, 420TVL, 0LUX, 24LED, 15-30M, Lens:3.6mm



12pcs outdoor cameras

1/4"SONY 420tvl,0lux, 36 IR leds 30 meter, waterproof IP66 w/3.6mm lens, Casing could be balck or silver

1pc 16ch DVR

Video Compression H.264
BNC 16ch input/2ch output, 1ch SPOT OUTPUT, 1ch VGA output
Audio Input/Output RCA 4ch input/2ch output
Real time dispay and record:480FPS(400FPS)
Recording Pack Time 15/30/45/60mins selectable
HDD Interface Support 2pcs x 1T SATA HDD & USB disk
Network Function Support to live view with IE & with Mobile phone
USB2.0 USB mouse, USB disk (backup, upgrade)
Senor & Alarm I/O 16 sensor inputs / 1 alarm output



Accessories:

50meter video+power Cable
8pcs 30meter video+power Cable
4pcs 20meter video+power Cable
2pcs 10meter video+power Cable
1pc 12V 10A 18channel power supply box
1pc DVR (BNC) to SCART cable for TV connection
1pc 1 metre crossed network patch lead
8pcs A4 size CCTV notification signs

2pcs

\$3,242.51

PC Cards & Misc

Model	Description	Price
DC10104	 <p>CCTV H.264 optimized 4 ch 50/ 60fps Netwrok DVR card with software, Resolution: 640x480, 352x288, 320x240 PCI Camera Input: 4 Channels Video Format: PAL/ NTSC Image Compression: H.264 Optimized Video Frame Rate: 25fps (PAL), 30fps (NTSC) Display Resolution: 640x480, 352x288, 320x240 Recording Resolution: 640x480, 352x288, 320x240 Compression Ratio: 30-100 M/H/C Motherboard Slot: PCI Network Protocol: TCP/ UDP Operating System: Windows XP/ VISTA 32</p>	\$94.90
DC9808	 <p>CCTV H.264 optimized 8 ch 200/ 240fps Netwrok DVR card with software, 9-bits ADCs Image quality, Resolution: 640x480, 352x288, 320x240 PCI Camera Input: 8 Channels Video Format: PAL/ NTSC Image Quality: 9-bits ADCs Super High Quality Image Compression: H.264 Optimized Video Frame Rate: 200fps (PAL), 240fps (NTSC) Display Resolution: 640x480, 352x288, 320x240 Recording Resolution: 640x480, 352x288, 320x240 Compression Ratio: 8-150 M//H/C Network Protocol: TCP/ UDP Operating System: Windows 2000/ XP/ VISTA 32</p>	\$262.85
EP-12VDC-8P4A (220VAC)	 <p>4 Amp 8 Channels 12VDC Regulated Distributed Power Supply Box with Reset-able Fuse Input Voltage: 220VAC Output Voltage: 12VDC 8 Individually outlet pairs Total Output: 4 Amp Max. Output Amperage: 0.65 Amp/ Ch. Integral Surge Protection Individual LED power indication Individual PTC Reset-able Fuses Output Protection An Internal Built ON/OFF switch Metal Case Size: 20cm x 14cm x 6cm (L x W x H)</p>	\$102.04